

C3W (ezGuard)

Dual Sound and Light Protection

An HD/Full HD Wi-Fi camera with active defense, two-way audio and a durable design for all-weather protection.

Key Features



720p/1080p



Supports 2.4GHz Wi-Fi (IEEE802.11b, 802.11g, 802.11n)



IP66 Dustproof and Waterproof



Supports MicroSD card slot Up to 128GB



Two-way audio. Pickup distance up to 5 meters.



True Day/Night camera with auto-switching. Infrared night vision up to 30 meters.



Active Defense



Active defense

Upon detection of suspicious activity, the C3W (ezGuard) activates a loud siren and strobe light to scare off intruders.

Two-way audio

The camera comes with a built-in microphone and HiFi quality speaker, enabling two-way audio via the camera and your phone or tablet.







Powerful, dual external antennas

It is equipped with powerful, dual external Wi-Fi antennas, for long-range transmission with strong penetration and anti-interference capabilities.

Security for all seasons

With an IP66-rated weatherproof design, the C3W (ezGuard) is a reliable and durable guard that can protect you in all types of weather: rain, sunshine or even snow.



30m night vision


The integration of efficient infrared lighting, an anti-reflection panel and ICR infrared filter enables excellent night vision up to 30 meters.



The C3W (ezGuard) watches for movement. It will take a picture and send alerts to your smartphone when it detects motions.

360° swivel and base

With a 360°swivel and base, the C3W (ezGuard) is ideal for both ceiling and wall-mounted installations.







Specifications Model CS-CV310-A0-1B2WFR/CS-CV310-A0-3B1WFR

Camera

Network

Image Sensor	1/2.7" Progressive Scan CMOS	Stora
Minimum illumination	0.02 lux @(F2.0, AGC ON), 0 lux with IR	Store
Shutter Speed	Self-adaptive shutter	Wi-Fi
Lens	2.8mm@ F2.2: Horizontal angle: 103°/92°	Proto
	Diagonal angle: 118°/108° 4mm@ F2.0: Horizontal angle: 87°/72°	Inter
	Diagonal angle: 104°/86° 6mm@ F2.0: Horizontal angle: 54°/36° Diagonal angle: 62°/42°	Gene
Lens Mount	M12	Comi
Day & Night	IR-cut filter	Minir Requ
DNR	3D DNR	
WDR	Digital WDR	Wi-F
		$\left(\right)$

Compression

Video Compression	H.264
Н.264 Туре	Main Profile
Video Bit Rate	HD, Balanced and Smooth. Adaptive bit rate.

Image

Max. Resolution	1920×1080/1280×720
Image Settings	Brightness, contrast, saturation, etc. (configurable via EZVIZ Studio)
BLC	Support

rage art Alarm Fi Pairing

tocol

erface Protocol

neral Features

nmunication Inte imum Network quirements

·Fi

Standard Frequency Range Channel Bandwidth Security **Transmission Rate**

General

Power Supply Power Consumption IP Grade IR Range Product Dimension Packaging Dimensi Weight

	Supports MicroSD card (max. 128GB)	
	Intelligent motion detection	
	SmartConfig (Wi-Fi One-Key Configuration) and AP paring	
	EZVIZ Cloud proprietary protocol	
	EZVIZ Cloud proprietary protocol	
	Anti-Flicker, Dual-Stream, Heartbeat Messages, Mirror Image, Password Protection, Watermark	
terface	RJ45 10M/100M self-adaptive Ethernet port*1	
r L	2M	
	IEEE802.11 b/g/n	
	2.4GHz ~ 2.4835 GHz	
h	Supports 20MHz	

	2.4GHz ~ 2.4835 GHz
1	Supports 20MHz
	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK
	11b: 11Mbps, 11g: 54Mbps, 11n: 150Mbps

	DC 12V±10%
on	Max. 6W
	IP66
	MAX. 30meters
ns	150.44mm x 85.80mm x 71.64mm
sions	252mm x 110mm x 92mm
	326g

Package Contents:

- C3W (ezGuard) X 1
- Power Adapter with 1.5 Meters Power Cable X 1
- Mounting Template X 1
- Screw Kit X 1
- Waterproof Kit X 1
- Quick Start Guide X

Requirements

- Operating Conditions: -30°C ~ 60°C, Humidity 95% or less (non-condensing)

Certificates

FCC/UL/IC/NOM/CE/RoHS/WEEE/REACH

Specifications are subject to change without notice. EZVIZ is a registered trademark of Hangzhou EZVIZ Network Co., Ltd. Other brands and product names are trademarks or registered trademarks of their respective holders.

https://www.ezvizlife.com/